

STOP SEARCHING, START BENDING

Stop wasting valuable machine time on disorganized tool hunts and risky manual handling. This Press Brake Change-Over Cart is a lean-inspired solution designed to bridge the gap between your central storage and the press brake. By staging up to 54 linear feet of punches and dies on a stable, ergonomic platform, you eliminate unnecessary motion and protect your tooling from accidental damage. Engineered for maximum durability and universal compatibility, this cart ensures your operators stay safe and your “green light” stays on.



- **Maximum Productivity:** Reduce setup time by staging tools and reducing motion; compatible with all styles of press brake tooling.
- **Superior Safety & Stability:** Features a wide-track wheelbase to prevent tip-overs and ergonomic shelving to promote safe lifting practices.
- **Heavy-Duty Construction:** Robotically MIG-welded steel with a 900 lb. caster capacity and a 75 lb. capacity drawer for precision instruments.
- **High Capacity:** Safely transport and organize up to 54 linear feet of tooling in one trip.

Technical Specifications

Feature	Specification
Cart Dimensions	39" wide x 27" deep x 38" tall
Shipping Weight	275 lbs.
Tooling Capacity	54 linear feet; Max. tool length of 36" [914mm]
Storage Drawer	35" x 16" x 3" with ball bearing slides (75 lb. capacity)
Safety Features	Wide-track anti-tip base; Ergonomic lifting heights
Mobility	Four 6" heavy-duty casters (900 lb. capacity ea.)
Caster Configuration	2 rigid; 2 swivel with brakes
Construction	Robotically MIG welded 16- & 18-gauge steel
Finish	Industrial grade durable powder coat

Ordering Information*

Cat. No.	Tool Style
990956	European Punch Tang: .500" [12.7mm]
990958	American Punch Tang: .512" [13mm]
990959	WT Punch Tang: .787" [20mm]

*Cart is only available for purchase in the North American market.

For more information, visit wilsontool.com/bending, call our tooling technicians at 800.445.4518 or contact your sales engineer.

© Wilson Tool International.
All rights reserved. B391F (3.2026)